

### **I-822 TA3**

<b>Overall</b>	<b>Length</b>	25' 9"
	<b>Width</b>	8'
	<b>Height</b>	8' 10"
<b>Interior</b>	<b>Length</b>	22' 4"
	<b>Width</b>	7' 5"
	<b>Height</b>	6' 8"
<b>Side wall</b>	<b>Height</b>	6' 1/2"
<b>Distance between w/w</b>		74"
<b>Rear Door</b>		Double
	<b>Width</b>	7' 4"
	<b>Height</b>	6'
<b>Hitch Weight</b>		315 lbs.
	<b>Height</b>	21"
	<b>Ball Size</b>	2 5/16"
<b>Platform height</b>		23"
<b>G.V.W.R.</b>		9,950 lbs.
<b>Curb Weight</b>		3,590 lbs.
<b>Payload Capacity</b>		6,810 lbs.
<b>Axles (single) Brakes</b>		5,200 lbs.
<b>Tires</b>		Electric
<b>Wheels</b>		ST225 75/r15 (d)
<b>Frame</b>		6 on 5 1/2
<b>Floor (16" o/c)</b>		8" I-Beam
<b>Side Walls (16" o/c)</b>		3/4" Drymax 3/8" plywood

**Specifications subject to change.**